


IMPIEGHI PRINCIPALI: Carri miscelatori verticali.  
 MAIN APPLICATION: Vertical agricultural mixer car.

X = Albero per ventola su richiesta del cliente  
 X = Fan shaft on request of customer

	RAPPORTO GEAR RATIO	GIRI ENTRATA INPUT REV.	POTENZA ENTRATA INPUT POWER		COPPIA TORQUE	Ø ALBERI SHAFTS Ø (mm)				GIRI USCITA OUTPUT REV.	PESO WEIGHT	
		giri/min - rpm	CV	kW	Nm	A	B	C	D	giri/min - rpm	kg	
MOLTIPLICATORI OVERDRIVE GEARS	1:9.2	540	45	34	64					4968	41	
	1:8.18	540	55	41	88					4417	OLIO/OIL SAE150	
	1:7	540	60	44	108					3780	SAE150 kg. 2	
	1:6.2	540	69	51	141					3348		
												cuscinetti bearings
												X 6308
												W 6307
												Y 6307
											Z 6307	

MATERIALI MATERIALS	ALBERI / SHAFTS	INGRANAGGI / GEARS	SCATOLA / BOX	DENTATURA / TOOTHING
	18NiCrMo5	18NiCrMo5	ghisa g25 cast iron g25	A denti elicoidali sbarbati C.T.R C.T.R helicoidal and shaved tooth



I gruppi vengono forniti senza olio; provvedere al riempimento fino al livello prima della messa in opera.  
 The units are supplied without oil; before use fill, at to the correct level.