


IMPIEGHI PRINCIPALI: Carri miscelatori verticali.
 MAIN APPLICATION: Vertical agricultural mixer car.

X = Albero per ventola su richiesta del cliente
 X = Fan shaft on request of customer

	RAPPORTO GEAR RATIO	GIRI ENTRATA INPUT REV.	POTENZA ENTRATA INPUT POWER		COPPIA TORQUE	Ø ALBERI SHAFTS Ø (mm)				GIRI USCITA OUTPUT REV.	PESO WEIGHT
		giri/min - rpm	CV	KW	Nm	A	B	C	D	giri/min - rpm	kg
MOLTIPLICATORI OVERDRIVE GEARS	1:1	540	85	62	1110					540	41
	1:1.52	540	90	67	755					820	
	1:2	540	87	65	554					1080	OLIO/OIL SAE150
	1:3	540	82	61	348					1620	SAE150 kg. 2
	1:3.8	540	78	58	260					2052	
	1:4	540	77	57	245					2160	
	1:5	540	75	55	191					2700	cuscinetti bearings
	1:6.2	540	69	51	141					3348	X 6308
	1:7	540	60	44	108					3780	W 6307
	1:8.2	540	55	41	88					4417	Y 6307
1:9.2	540	45	34	64					4968	Z 6307	

MATERIALI MATERIALS	ALBERI / SHAFTS	INGRANAGGI / GEARS	SCATOLA / BOX	DENTATURA / TOOTHING
	18NiCrMo5	18NiCrMo5	ghisa g25 cast iron g25	A denti elicoidali sbarbati C.T.R C.T.R helicoidal and shaved tooth



I gruppi vengono forniti senza olio; prevedere al riempimento fino al livello prima della messa in opera.
 The units are supplied without oil; before use fill, at to the correct level.