


IMPIEGHI PRINCIPALI: Carri miscelatori verticali.  
 MAIN APPLICATION: Vertical agricultural mixer car.

X = Albero per ventola su richiesta del cliente  
 X = Fan shaft on request of customer

	RAPPORTO GEAR RATIO	GIRI ENTRATA INPUT REV.	POTENZA ENTRATA INPUT POWER		COPPIA TORQUE	Ø ALBERI SHAFTS Ø (mm)				GIRI USCITA OUTPUT REV.	PESO WEIGHT
		giri/min - rpm	CV	KW	Nm	A	B	C	D	giri/min - rpm	kg
RIDUTTORI REDUCTION GEARS	1:1	540	85	62	1110					540	41
	1.152:1	540	60	44	1163					355	
	2:1	540	46	34	1172					270	OLIO/OIL SAE150
	3:1	540	28	21	1070					180	SAE150 kg. 2
	3.8:1	540	22	16	1065					142.1	
	4:1	540	21	15.5	1069					135	
	5:1	540	17	12.5	1083					108	cuscinetti bearings
	6.2:1	540	14	10.3	1108					87	X 6308
	7:1	540	12	8.5	1070					77.1	W 6307
	8.2:1	540	11	8	1147					66	Y 6307
	9.2:1	540	9	7	1050					58.7	Z 6307

MATERIALI MATERIALS	ALBERI / SHAFTS	INGRANAGGI / GEARS	SCATOLA / BOX	DENTATURA / TOOTHING
	18NiCrMo5	18NiCrMo5	ghisa g25 cast iron g25	A denti elicoidali sbarbati C.T.R C.T.R helicoidal and shaved tooth



I gruppi vengono forniti senza olio; prevedere al riempimento fino al livello prima della messa in opera.  
 The units are supplied without oil; before use fill, at to the correct level.